

EV 1018-C

CE ROSH EMC



Input Voltage : AC100V~AC240V, 50/60Hz;
Power Consumption : 180W;
Lamp Specifications: 18pcs 10W four in one RGBW (optional: RGBWA five in one)
high-efficiency
LED, rated life 50000 hours;
Lens Angle: 25° (optional: 45°) ;
Spot Angle: 40°;

Color: RGBW linear color mixing ;
Color Temperature : color cast calibration setting 、 color temperature
output inside device;
Dimmer: 0-100% linearly dimming ,
5 dimmer modes:32-bits dimming, still keep smooth dimming when changing
at the range of low DMX value ;
Refresh Frequency:1800Hz, no blink when camera shooting;
Shutter: independent electronic strobe ;
Control Mode:
Standard DMX512, 3 pin interfaces ;
4 Channel modes ;
Master/slave mode, no need to set up the master and slave manually, will
receive the main engine data automatically ;
5 auto-running modes, rainbow channel and rainbow effect ;
Sound active mode;
Other Functions:
Self-programming function,5 chases, each chase has 20 scenes, fade
function; Projector setting data、 self-programming data can be download-
ed each other ;

Temperature Control Protection: Fan cool, dynamic fan speed modulation
versus temperature.

Waterproof Grade : IP20

Work Environment Temperature : -20° C ~ 40° C;

Net Weight : 4.0Kg;



DIMENSION

