



# EV 354-C

CE ROHS EMC



Input Voltage : AC100V~AC240V, 50/60Hz;  
 Power Consumption : 170W;  
 Lamp Specifications : 54 pcs 3W ( 12R+14G+14B+14W) high-efficiency LED, rated life 50000 hours;  
 Lens Angle: 25° ( optional: 15° 、 45° ) ;  
 Spot Angle: 40°;

Color: RGBW linear color mixing ;  
 Color Temperature : color cast calibration setting 、 color temperature output inside device ;  
 Dimmer: 0-100% linearly dimming ,  
 5 dimmer modes:32-bits dimming, still keep smooth dimming when changing at the range of low DMX value ;  
 Refresh Frequency:1800Hz, no blink when camera shooting;  
 Shutter: independent electronic strobe ;  
 Control Mode:  
 Standard DMX512, 3 pin interfaces ;  
 4 Channel modes ;  
 Master/slave mode, no need to set up the master and slave manually, will receive the main engine data automatically ;  
 5 auto-running modes, rainbow channel and rainbow effect ;  
 Sound active mode;  
 Other Functions :  
 Self-programming function, 5 chases, each chase has 20 scenes, fade function; Projector setting data. self-programming data can be downloaded each other ;

Temperature Control Protection: Fan cool, dynamic fan speed modulation versus temperature.  
 Waterproof Grade : IP20  
 Work Environment Temperature : -20° C ~ 40° C ;  
 Net Weight : 2.4Kg;



## DIMENSION

